

JETTA 303 SEMI FLUID GREASE

Lithium Complex Semi-Fluid Grease · NLGI 00

DESCRIPTION

A lithium-complex semi-fluid NLGI 00 grease, specially developed as a multi-purpose lubricant on a heavy base oil for industrial applications. It has shown exceptional performance, providing extended lubrication intervals over a wide operating temperature range (-15 °C to 130 °C).

PACK SIZES

Multiple pack sizes available on request.

APPLICATIONS

- Lubrication of spur gears with steel/steel friction surfaces
- Sliding and roller bearings re-lubricated through pipes and fittings
- Spur, bevel and worm gears under normal and more difficult operating conditions

COST-SAVING BENEFITS

- Versatile usage in industrial gears
- Direct contact with water possible
- Applicable under heavy operating conditions
- Long lifetime of machine parts

TYPICAL DATA

PROPERTY	TYPICAL VALUE
Thickener	Lithium Complex
Texture	Smooth
Colour	Red
NLGI grade	00
Base oil viscosity at 40 °C (IP 71)	900 cSt
Four-ball weld load (ASTM D2596)	400 kg
Four-ball wear scar (ASTM D2266)	0.5 mm
Timken OK load (ASTM D2509)	20/45

Typical values shown do not constitute a specification. The information is based on current knowledge and is intended to describe the product for possible applications; it does not release the user from performing preliminary tests.