

JETTA OG 1000

Extreme-Pressure Gear Oil · ISO VG 1000

DESCRIPTION

JETTA OG 1000 is a lubricating oil for gearboxes formulated with extreme-pressure, anti-wear, anti-foam, anti-oxidation and anti-corrosion additives. Its high viscosity index allows operation at both low and high temperatures.

PACK SIZES

Multiple pack sizes available on request.

APPLICATIONS

- All types of reduction gears: spur, helical, hypoid, bevel and worm
- Dip or circulation lubrication of bearings and plain bearings
- Heavy industries, harbour installations, cement and mechanical industries
- Where an extreme-pressure, long-term lubricant is required over a large temperature range

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
Base oil	-	-	Mineral
Kinematic viscosity at 40 °C	NF T 60-100	cSt	1000
Viscosity index	NF T 60-136	-	98
Colour	NF T 60-104	-	>8
Density	NF T 60-101	kg/m ³	932
Flash point	NF T 60-118	°C	255
Drop point	NF T 60-105	°C	-3
Copper corrosion	NF M 07-015	-	1b
Aniline point	NF M 07-021	°C	101
FZG test (A/16.6/140 °C)	DIN 51357	-	>12

Typical values shown do not constitute a specification. The information is based on current knowledge and is intended to describe the product for possible applications; it does not release the user from performing preliminary tests.